

HP LaserJet Pro M402dne Printer (C5J91A)

190,700 AMD

Specifications	
Print speed black	Up to 38 ppm
First page out ready	Black: As fast as 5.7 sec
Print quality (best)	HP FastRes 1200
Print Resolution Technologies	HP FastRes 1200, HP ProRes 1200, 600 dpi
Duty cycle (monthly, A4)	Up to 80,000 pages
Recommended monthly page volume	750 to 4,000
Standard memory	256 MB DRAM; 256 MB NAND Flash
Processor speed	1200 MHz
Display	2-line backlit LCD graphic display
Print languages	HP PCL 5, HP PCL 6, HP Postscript Level 3 emulation, direct PDF (v1.7) printing, URF, PCLM, PWG
Paper handling	
Paper handling input, standard	100-sheet multipurpose tray 1 250-sheet input tray 2
Paper handling input, optional	Optional third 550-sheet tray
Paper handling output, standard	150-sheet output bin
Maximum output capacity (sheets)	Up to 150 sheets
Duplex printing	Automatic (standard)
Media sizes supported	Tray 1: A4, A5, A6, A5-R, B5 (JIS), B6 (JIS), envelope B5, C5, DL, custom size Tray 2 & Tray 3: A4, A5, A6, A5-R, B5 (JIS), B6 (JIS), custom size
Media sizes, custom	Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 355.6 mm
Media types	Paper (plain, EcoFFICIENT, light, heavy, bond, coloured, letterhead, preprinted, prepunched, recycled, rough), envelopes, labels, transparencies
Supported media weight	Tray 1: 60 to 175 g/m ² ; Tray 2, optional 550-sheet Tray 3: 60 to 120 g/m ²
Connectivity	
Standard connectivity	1 Hi-Speed USB 2.0 1 Host USB 1 Gigabit Ethernet 10/100/1000T network

Mobile printing capability	HP ePrint Apple AirPrint [™] , Mopria [™] -certified Google Cloud Print 2.0 Mobile Apps
Wireless capability	No
Dimensions and Weight	
Minimum dimensions (W x D x H)	381 x 357 x 216 mm
Maximum dimensions (W x D x H)	381 x 634 x 241 mm
Product weight	8.58 kg
Power and operating requirements	
Power requirements	Input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz)
Power consumption	591 watts (printing), 6.1 watts (ready), 2.8 watts (sleep), 0.6 watts (Auto-On/Auto-Off, via USB connectivity), 0.1 watts (off)
Recommended operating temperature range	15 to 32.5°C
Recommended humidity operating	30 to 70% RH
What's included	
Cable included	No
What's in the box	HP LaserJet Pro M402dne Preinstalled HP 26A Black LaserJet Toner Cartridge (3,100 pages) Getting Started Guide Setup poster Support flyer Warranty guide Printer documentation and software on CD-ROM Power cord
Warranty	1 Year Limited Warranty