

# HPE X130 10G SFP+ LC SR Transceiver (JD092B)

423,200 AMD

<b>Cabling</b>	<p>Cable type: 62.5/125 <math>\mu\text{m}</math> or 50/125 <math>\mu\text{m}</math> (core/cladding) diameter, graded-index, low metal content, multimode fiber optic, complying with ITU-T G.651 and ISO/IEC 793-2 Type A1b or A1a, respectively; Maximum distance:  <ul style="list-style-type: none"> <li>â€¢ 2-26m with 62.5 <math>\mu\text{m}</math> multimode cable @ 160 MHz*km</li> <li>â€¢ 2-33m with 62.5 <math>\mu\text{m}</math> multimode cable @ 200 MHz*km</li> <li>â€¢ 2-66m with 50 <math>\mu\text{m}</math> multimode cable @ 400 MHz*km</li> <li>â€¢ 2-82m with 50 <math>\mu\text{m}</math> multimode cable @ 500 MHz*km</li> <li>â€¢ 2-300m with 50 <math>\mu\text{m}</math> multimode cable @ 2000 MHz*km</li> <li>â€¢ 2-400m with 50 <math>\mu\text{m}</math> multimode cable @ 4700 MHz*km</li> </ul> </p>
<b>Ports</b>	<p>1 LC 10-GbE port (IEEE 802.3ae Type 10GBASE-SR); Duplex: full only Fiber type Multi Mode</p>