

Kyocera ECOSYS P3060dn

486,300 AMD ~~610,500 AMD~~

GENERAL

General type	Monochrome printer for A4 formats
Technology	KYOCERA ECOSYS Laser
Control panel	5 line LCD back lit display with alphanumeric keypad
Engine speed	Up to 60 pages per minute in A4 and A5
Resolution	1,200 dpi
Duty cycle	Max. 275,000 pages per month
Warm-up time	Approx. 25 seconds or less from power on
Time to first print	Approx. 4.9 seconds or less
	380 mm x 410 mm x 320 mm
Weight	Approx. 15.5 kg
	Printing: 684 W, Ready mode: 11 W, Sleep-mode: 0,8 W
Power source	220 ~ 240 V, 50/60 Hz
Noise (ISO 7779)	Noise (Sound pressure level: ISO 7779 / ISO 9296) Printing (BW/Colour) 56 dB(A) LpA Quiet Mode: 51.5 dB(A) LpA Ready mode: 27.1 dB(A) LpA Sleep mode: Immeasurably low
Safety standards	TÃœV-GS, CE- This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard.
Dimensions General (W x D x H) memory Power	Standard 512 MB RAM, max. 2,560 MB RAM

PAPER HANDLING

Input capacity	100-sheet multi-purpose tray; 60â€“220 g/m2; A4, A5, A6, B5, Letter, Legal, Custom (70 x 148 â€“ 216 x 356 mm) 500-sheet universal paper cassette, 60 â€“ 120 g/m2; A4, A5, A6, B5, Letter, Legal, Custom (105 x 148 â€“ 216 x 356 mm)
Max. input capacity with options	2,600 sheets

Duplex unit	Duplex functionality as standard: Double-sided printing A4, A5, B5, Letter, Legal, Custom (140 x 210 mm â€“ 216 x 356 mm), 60â€“120 g/mÂ²
Max. output capacity	500-sheet-face-down with paper full sensor and optional 250-sheet-face-up with PT-320
General paper handling	All paper capacities quoted are based on a paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

PRINT

Processor	1.2 GHz
Controller language	PRESCRIBE IIe
Emulations	PCL6 (PCL5c / PCL-XL), PostScript* 3 (KPDL 3), XPS Direct Print, PDF Direct Print 1.7, IBM Proprinter X24E, Epson LQ-850 with automatic emulation sensing
Fonts	93 scalable fonts for PCL/PostScriptÂ®, 8 fonts for Windows VistaÂ®, 1 Bitmap font, 45 barcodes (e.g. EAN 8, EAN 13, EAN 128) with automatic generation of checksums as well as support of two-dimensional barcodes PDF-417 under PRESCRIBE (PCL and other barcodes available as an option)
Features	Security features: IPsec, HTTPS, SNMPv3, IPPS, Encrypted PDF Direct Print, Private Print, Secure printing via SSL, POP over SSL, SMTP over SSL, Access control via 100 integrated department codes. Data Security Kit (E) protects data on the optional SSD.
Protocol	Mobile printing support: KYOCERA Mobile Print app for iOS and Android, AirPrint (requires firmware update), Mopria, Google Cloud Print
Applicable OS	All current Windows operating systems, Mac OS X Version 10.8 or higher, UNIX, LINUX as well as other operating systems on request

INTERFACES

Standard interface	USB 2.0 (Hi-Speed), 2 USB Host Interfaces, Gigabit Ethernet (10/100/1000BaseT), Slot for optional internal print server or SSD hard disc, Slot for optional SD/SDHC-Card
--------------------	--

Consumables

TK-3190	Microfine toner for 25,000 pages A4. Capacity of starter toner is 10000 pages A4. Average continuous toner yield in accordance with ISO/IEC 19752
TK-3170	Microfine toner for 15,500 pages A4. Average continuous toner yield in accordance with ISO/IEC 19752
TK-3160	Microfine toner for 12,500 pages A4. Average continuous toner yield in accordance with ISO/IEC 19752

WARRANTY

Warranty	1-year warranty as standard (depending on the country). KYOCERA guarantees the drums and developers for 3 years or maximum 500,000 pages (whichever occurs sooner), provided the printer is used and cleaned in accordance with the service instructions.
----------	---