

APC Back-UPS 1100VA (BX1100CI-RS)

103,000 AMD

Output	
Output Power Capacity	660 Watts / 1100 VA
Nominal Output Voltage	230V
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Topology	Line Interactive
Waveform Type	Stepped approximation to a sinewave
Output Connections	(4) Schuko CEE 7 (Battery Backup)
Input	
Nominal Input Voltage	230V
Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	Schuko CEE 7/7P
Input voltage range for main operations	150 - 280 V
Cord Length	1.16 meters
Batteries & Runtime	
Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	8 hour(s)
Typical Backup Time at Half Load	11 min (330 Watts)
Typical Backup Time at Full Load	2.4 min (660 Watts)
Replacement Battery	APCRBC113
RBC Quantity	1
Communications & Management	
Interface Port(s)	USB
Control panel	LED Status display with On Line : On Battery
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Surge Protection and Filtering	
Surge energy rating	273 Joules
Physical	
Maximum Height	21.5 cm
Maximum Width	13 cm
Maximum Depth	33.6 cm
Net Weight	12 kg
Environmental	
Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95%
Operating Elevation	0 - 3000 meters
Storage Temperature	-15 to 40 °C

Audible noise at 1 meter from surface of unit	45.0 dBA
Warranty	2 year warranty